

## The thirst quencher!

- Lead free waterways
- Available as cool and cold, or hot and cold
- Floor standing or counter top
- User adjustable thermostat
- User friendly fuse
- Stainless steel reservoir
- Fully recessed alcove
- Wide removable drip tray and grid
- Hideaway control compartment
- Thermoplastic self closing taps
- Hot water safety tap
- Optional water protection system
- UV protected plastic and powder painted steel cabinet
- Cloud white finish
- Unique "function status display" lamps
- Envious serviceability



Bottled water coolers are proven performers in Australia's harsh climatic conditions. These units are innovators of advanced engineering, durability and classic refined styling.



## The Water Filter Shop

93 Ingham Rd, Townsville, 4810  
Phone: (07) 47712677  
Fax: (07) 47211616  
PO Box 5302, Townsville 4814  
Email:  
info@thewaterfiltershop.com.au

## FEATURES AND SPECIFICATIONS

**B5 BOTTLED WATER COOLERS**  
Free Standing and Benchtap

### GENERAL

The Waterworks® new generation bottled water dispensers continue to lead the way with advanced technological innovations. Refined yet durable, they have a captivating modern style which harmonises with a variety of decors. They are engineered to the highest levels of quality dependability and service and are the proven performers in Australia's harsh climatic conditions.

### CONSTRUCTION

**COLD WATER RESERVOIR:** Type 304 stainless steel tank, which provides superior chilling. The highly polished surface is easy to clean and maintain. Easy to replace insulation.

**HOT TANK:** Type 304 stainless steel. 500 Watt sheathed heater installed in the tank ensures accurate temperature control. On/Off switch is easily accessible at side of cabinet. Tank capacity is 2 litres.

**CABINET:** Top and front panels are moulded of UV treated ABS and side panels are zinc coated steel sheets covered in electrostatically applied high polymer polyester resin.

**COLOUR:** High gloss cloud white available as standard.

**TAPS:** Durable polypropylene self-closing design – easy to operate. They are fully recessed for protection and are lever type, with fast flow for ease of operation. Hot tap has safety influence.

**FUNCTION STATUS DISPLAY:** Waterwork's unique design. This exclusive device illuminates a green and red signal indicating the power/hot/cold position of the dispenser.

### OPTIONS

**NO SPLASH VALVE:** Allows the bottle to be changed without excess spillage. Just place the bottle on the cooler and the valve opens to let water through. If you need to remove the bottle, the valve automatically closes. The water flow is more constant and therefore there is less cyclic stress on the bottle for added safety against bottle fractures.

**"AQUA SENTRY" WATER PROTECTION SYSTEM:** Snap on Aqua Sentry is an additional assurance of water quality. A specially designed resealable plug is controlled by a feed tube which prevents the outside of the bottle coming in contact with the water.

### SPECIFICATIONS

**REFRIGERATION SYSTEM:** CFC-free refrigerant which is non-toxic, non-flammable and non-ozone depleting. Refrigerant flow is controlled by capillary tube which has no moving parts. The compressor is hermetically sealed with automatic overload protection. Lubricant is not needed.

**CONDENSER:** Quiet operating air-cooled static type. No moving parts.

**THERMOSTAT:** Adjustable and user friendly. Readily accessible at side of cabinet.

#### PERFORMANCE:

Tap 1                      Outlet water 9°C approx.  
Tap 2                      Outlet water 18°C approx.  
Hot Tap                    Outlet water 92°C approx.

#### CAPACITIES CHART:\*

Room Temp °C	21	27	32
150ml Cups/hr 10°C	44	32	18
Litre/hr at 10°C	4.2	3.1	1.8

**HOT WATER DELIVERY:** 45 x 170ml cups per hour

\*Intermittent use only, continuous use will result in reduced performance.

**ELECTRICAL:** 220 Volts 50Hz single phase. A 1.8 metre house cable and 3 pin plug is supplied. Full load current is 1.2 amps.

#### SHIPPING WEIGHT:

B5C:                      19kg                      SB5C:                      14kg  
BB5CH:                    21kg                      SB5CH:                    16kg

#### DIMENSIONS:

B5C/B5CH:                    310mmW x 310mmD x 950mmH  
SB5C/SB5CH:                    310mmW x 310mmD x 534mmH

**QUALITY:** The specifications of these coolers are manufactured to comply with the standards of underwriters laboratories.

**WARRANTY:** Two years parts and labour.



### The Water Filter Shop

93 Ingham Rd, Townsville, 4810  
Phone: (07) 47712677  
Fax: (07) 47211616  
PO Box 5302, Townsville 4814  
Email:  
info@thewaterfiltershop.com.au

**DISTRIBUTED BY:**